



Part Number	Stranding	Conductor	Nominal Outer Diameter (inches)	Nominal Outer Diameter (mm)	Weight Lb/1000ft
1000404	4AWG (259 x 28) Bare Copper	4	1.058	26.87	905

**Recommended Applications:**  
 Machine tools, CNC machines, grinding machines, woodworking machinery, control panel to machine connections. Plus extremely light flexing applications.

**Basic Construction:**  
 Fine bare copper strands

**Insulating Compound:**  
 Specially formulated oil resistant PVC

**Colour Code:**  
 Black with white number coding. Conductor count for three conductor cable and beyond includes a green/yellow ground conductor (minimum 30% coverage).

**Jacketing Compound:**  
 Specially formulated oil resistant PVC

**Minimum Bend Radius:**  
 For installation only 4 x cable diameter

**Nominal Voltage Rating:**  
 600V

**Temperature Range:**  
 For static applications -40C to +90C

**Approvals:**  
 AWM 21098, 90C, 600V, 60C OIL, 235992 CSA, UL, AWM I/II, A/B, 90C, 600V, CE, OIL RES, RoHS compliant  
 Conforms to CE low voltage directive  
 Cable now being produced with CSA FT4 rating

1.888.668.3539      289.337.9500      flex@awpinc.com

