



| Part Number | Stranding | Conductor | Nominal Outer Diameter (inches) | Nominal Outer Diameter (mm) | Weight Lb/1000ft |
|-------------|-----------------------------|-----------|---------------------------------|-----------------------------|------------------|
| 1001603 | 16AWG (26 x 30) Bare Copper | 3 | 0.284 | 7.21 | 60 |

Recommended Applications:

Machine tools, CNC machines, grinding machines, woodworking machinery, control panel to machine connections. Plus extremely light flexing applications.

Basic Construction:

Fine bare copper strands

Insulating Compound:

Specially formulated oil resistant PVC

Colour Code:

Black with white number coding. Conductor count for three conductor cable and beyond includes a green/yellow ground conductor (minimum 30% coverage).

Jacketing Compound:

Specially formulated oil resistant PVC

Minimum Bend Radius:

For installation only 4 x cable diameter

Nominal Voltage Rating:

600V

Temperature Range:

For static applications -40C to +90C

Approvals:

AWM 21098, 90C, 600V, 60C OIL, 235992 CSA, UL, AWM I/II, A/B, 90C, 600V, CE, OIL RES, RoHS compliant
Conforms to CE low voltage directive
Cable now being produced with CSA FT4 rating

1.888.668.3539

289.337.9500

flex@awpinc.com

