LF101B Blue Light Flex Control Cable

LF101B BLUE AWP PT #1011418B

Part Number	Stranding	Conductor	Nominal Outer Diameter (inches)	Nominal Outer Diameter (mm)	Weight Lb/1000ft
1011418B	14AWG (41 x 30) Bare Copper	18	0.742	18.85	480

Recommended Applications:
Machine tools, CNC machines, grinding machines, woodworking machinery, control panel to machine connections. Plus extremely light flexing applications.

Basic Construction:
Fine bare copper strands

Insulating Compound:
Specially formulated oil resistant PVC

Colour Code:
Blue with white number coding. Conductor count for three conductor cable and beyond includes a green/yellow ground conductor (minimum 30% coverage).

Jacketing Compound:
Specially formulated oil resistant PVC

Minimum Bend Radius:
For installation only 4 x cable diameter

Nominal Voltage Rating:
600V

Temperature Range:
For static applications -40C to +90C

Approvals:
AWM 21098, 90C, 600V, 60C OIL, 235992 CSA, UL, AWM I/II, A/B, 90C, 600V, CE, OIL RES, RoHS compliant
Conforms to CE low voltage directive
Cable now being produced with CSA FT4 rating

1.888.668.3539 289.337.9500 flex@awpinc.com